





WOOD



For hand-held and plunge circular saws



D	B	b	d	Z	Tooth Shape	Hook	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
mm	mm	mm	mm		A1						
120	1,8	1,3	20	12	ATB	15°	•••	•	-	FR02W001H	F03FS09663
120	1,8	1,3	20	40	ATB	5°	•	•••	-	FR02W002H	F03FS09664
130	2,4	1,6	20	24	ATB	15°	••	••	2/6/32,5	FR03W001H	F03FS09665
130	2,4	1,6	20	36	ATB	5°	•	•••	2/6/32,5	FR03W002H	F03FS09666
140	1,8	1,3	20	24	ATB	15°	•••	•	2/6/32,5	FR04W001H	F03FS09667
140	1,8	1,3	20	36	ATB	10°	••	••	2/6/32,5	FR04W002H	F03FS09668
140	1,8	1,3	20	42	ATB	5°	•	•••	2/6/32,5	FR04W003H	F03FS09669
150	2,4	1,6	16	24	ATB	15°	•••	•	2/6/32,5	FR05W001H	F03FS09670
150	2,4	1,6	20	24	ATB	15°	•••	•	2/6/32,5	FR05W002H	F03FS09671




	D	B	b	d	Z	Tooth Shape	Hook	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
	mm	mm	mm	mm			A1					
	150	2,4	1,6	20	42	ATB	5°	•	•••	2/6/32,5	FR05W003H	F03FS09672
	160	2,4	1,6	16	24	ATB	15°	•••	•	2/6/32,5	FR06W001H	F03FS09673
	160	2,4	1,6	16	48	ATB	5°	•	•••	2/6/32,5	FR06W002H	F03FS09674
	160	1,8	1,3	20	24	ATB	15°	•••	•	2/6/32,5	FR06W003H	F03FS09675
	160	1,8	1,3	20	36	ATB	10°	••	••	2/6/32,5	FR06W004H	F03FS09676
	160	1,8	1,3	20	48	ATB	5°	•	•••	2/6/32,5	FR06W005H	F03FS09677
	160	2,2	1,6	20	24	ATB	15°	•••	•	2/6/32,5	FR06W006H	F03FS09678
	160	2,2	1,6	20	36	ATB	10°	••	••	2/6/32,5	FR06W007H	F03FS09679
	160	2,2	1,6	20	48	ATB	5°	•	•••	2/6/32,5	FR06W008H	F03FS09680
	160	2,4	1,6	20	24	ATB	15°	•••	•	2/6/32,5	FR06W009H	F03FS09681
	160	2,4	1,6	20	36	ATB	10°	••	••	2/6/32,5	FR06W010H	F03FS09682
	160	2,4	1,6	20	48	ATB	5°	•	•••	2/6/32,5	FR06W011H	F03FS09683
	160	2,4	1,6	30	24	ATB	15°	•••	•	2/6/42	FR06W012H	F03FS09684
	160	2,4	1,6	30	48	ATB	5°	•	•••	2/6/42	FR06W013H	F03FS09685
	165	1,7	1,3	20	12	ATB	20°	•••	•	-	FR07W009H	F03FS10040
	165	1,7	1,3	20	24	ATB	15°	•••	•	-	FR07W001H	F03FS09686
	165	1,7	1,3	20	40	ATB	18°	•	•••	-	FR07W002H	F03FS09687
	165	2,4	1,6	20	24	ATB	15°	•••	•	2/6/32,5	FR07W003H	F03FS09688
	165	2,4	1,6	20	36	ATB	10°	••	••	2/6/32,5	FR07W004H	F03FS09689
	165	2,4	1,6	20	48	ATB	5°	•	•••	2/6/32,5	FR07W005H	F03FS09690
	165	2,4	1,6	30	24	ATB	15°	•••	•	2/7/42	FR07W006H	F03FS09691
	165	2,4	1,6	30	36	ATB	10°	••	••	2/7/42	FR07W007H	F03FS09692
	165	2,4	1,6	30	48	ATB	5°	•	•••	2/7/42	FR07W008H	F03FS09693
	170	2,4	1,6	30	40	ATB	10°	••	••	2/7/42	FR08W002H	F03FS09695
	180	2,4	1,6	20	24	ATB	15°	•••	•	2/6/32,5	FR09W001H	F03FS09696
	180	2,4	1,6	20	48	ATB	5°	•	•••	2/6/32,5	FR09W002H	F03FS09697
	180	2,4	1,6	30	24	ATB	15°	•••	•	2/7/42	FR09W003H	F03FS09698
	180	2,4	1,6	30	48	ATB	5°	•	•••	2/7/42	FR09W004H	F03FS09699
	182	1,7	1,3	19,05	30	ATB	15°	•••	•	-	FR10W001H	F03FS09700
	182	1,7	1,3	19,05	40	ATB	15°	••	••	-	FR10W002H	F03FS09701
	182	1,7	1,3	19,05	60	ATB	15°	•	•••	-	FR10W003H	F03FS09702
	184	2,4	1,6	16	24	ATB	15°	•••	•	2/6/32,5	FR11W001H	F03FS09703
	184	2,4	1,6	16	40	ATB	10°	••	••	2/6/32,5	FR11W002H	F03FS09704
	184	2,4	1,6	30	24	ATB	15°	•••	•	2/7/42	FR11W007H	F03FS09709
	190	2,4	1,6	16	24	ATB	15°	•••	•	2/6/32,5	FR13W001H	F03FS09712
	190	2,4	1,6	16	48	ATB	10°	•	•••	2/6/32,5	FR13W002H	F03FS09713
	190	2,4	1,6	20	24	ATB	15°	•••	•	2/6/32,5	FR13W003H	F03FS09714
	190	2,4	1,6	20	48	ATB	10°	•	•••	2/6/32,5	FR13W004H	F03FS09715
	190	2,4	1,6	20	56	ATB	5°	•	•••	2/6/32,5	FR13W005H	F03FS09716
	190	2,4	1,6	30	24	ATB	15°	•••	•	2/7/42	FR13W006H	F03FS09717
	190	2,4	1,6	30	40	ATB	10°	••	••	2/7/42	FR13W007H	F03FS09718
	190	2,4	1,6	30	48	ATB	10°	•	•••	2/7/42	FR13W008H	F03FS09719
	190	2,4	1,6	30	56	ATB	5°	•	•••	2/7/42	FR13W009H	F03FS09720
	200	2,4	1,6	30	24	ATB	15°	•••	•	2/7/42	FR14W001H	F03FS09721
	200	2,4	1,6	30	48	ATB	10°	•	•••	2/7/42	FR14W002H	F03FS09722
	210	2,4	1,8	30	24	ATB	15°	•••	•	2/7/42	FR15W003H	F03FS09725
	210	2,4	1,8	30	40	ATB	15°	••	••	2/7/42	FR15W001H	F03FS09723

D	B	b	d	Z	Tooth Shape	Hook	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
mm	mm	mm	mm			A1					
210	2,4	1,8	30	48	ATB	10°	•	•••	2/7/42	FR15W004H	F03FS09726
210	2,4	1,8	30	56	ATB	5°	•	•••	2/7/42	FR15W002H	F03FS09724
230	2,8	1,8	30	24	ATB	15°	•••	•	2/6/42	FR19W001H	F03FS09728
230	2,8	1,8	30	36	ATB	15°	••	••	2/7/42	FR19W002H	F03FS09729
230	2,8	1,8	30	48	ATB	15°	••	••	2/7/42	FR19W003H	F03FS09730
235	2,8	1,8	30	24	ATB	15°	•••	•	2/6/42	FR20W003H	F03FS09733
235	2,8	1,8	30	36	ATB	15°	••	••	2/7/42	FR20W004H	F03FS09734
235	2,8	1,8	30	48	ATB	15°	••	••	2/7/42	FR20W005H	F03FS09735
235	2,8	1,8	30	56	ATB	10°	•	•••	2/7/42	FR20W006H	F03FS09736
237	2,5	1,8	30	24	ATB	15°	•••	•	2/7/42	FR21W001H	F03FS09737
237	2,5	1,8	30	56	ATB	10°	•	•••	2/7/42	FR21W002H	F03FS09738
240	2,8	1,8	30	48	ATB	15°	••	••	2/7/42	FR22W001H	F03FS09739
270	2,8	1,8	30	60	ATB	10°	••	••	FT121	FR27W001H	F03FS09740
350	3,5	2,2	30	24	ATB	20°	•••	•	2/7/42	FR32W001H	F03FS09742
355	3,0	2,2	30	60	ATB	15°	•••	•	FT121	FR33W001H	F03FS09743

FT121: 2/7/42 + 2/9/46 + 2/9,5/46,5 + 2/10/60




For cordless hand-held
and plunge circular saws



D	B	b	d	Z	Tooth Shape	Hook	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
mm	mm	mm	mm			A1					
120	1,7	1,2	20	24	ATB	20°	••	••	-	FR02W003HC	F03FS10043
136	1,5	1,0	20	24	ATB	20°	••	••	-	FR03W003HC	F03FS10044
140	1,8	1,3	20	24	ATB	15°	•••	•	-	FR04W004HC	F03FS10045
140	1,8	1,3	20	42	ATB	5°	•	•••	-	FR04W005HC	F03FS10046
160	1,5	1,0	20	24	ATB	25°	•••	•	-	FR05W015HC	F03FS10048
160	1,5	1,0	20	36	ATB	15°	••	••	-	FR05W016HC	F03FS10049
160	1,5	1,0	20	48	ATB	10°	•	•••	-	FR05W017HC	F03FS10050
160	1,8	1,3	20	24	ATB	15°	•••	•	2/6/32,5	FR06W003H	F03FS09675
160	1,8	1,3	20	36	ATB	10°	••	••	2/6/32,5	FR06W004H	F03FS09676
160	1,8	1,3	20	48	ATB	5°	•	•••	2/6/32,5	FR06W005H	F03FS09677
160	2,2	1,6	20	24	ATB	15°	•••	•	2/6/32,5	FR06W006H	F03FS09678
160	2,2	1,6	20	36	ATB	10°	••	••	2/6/32,5	FR06W007H	F03FS09679
160	2,2	1,6	20	48	ATB	5°	•	•••	2/6/32,5	FR06W008H	F03FS09680
165	1,5	1,0	20	12	ATB	25°	•••	•	-	FR07W009HC	F03FS10051
165	1,5	1,0	20	24	ATB	25°	•••	•	-	FR07W010HC	F03FS10052
165	1,5	1,0	20	36	ATB	15°	••	••	-	FR07W011HC	F03FS10053
165	1,5	1,0	20	48	ATB	10°	•	•••	-	FR07W012HC	F03FS10054
165	1,7	1,3	20	12	ATB	20°	•••	•	-	FR07W009H	F03FS10040
165	1,7	1,3	20	24	ATB	15°	•••	•	-	FR07W001H	F03FS09686
165	1,7	1,3	20	40	ATB	18°	•	•••	-	FR07W002H	F03FS09687
182	1,7	1,3	19,05	30	ATB	15°	•••	•	-	FR10W001H	F03FS09700

D	B	b	d	Z	Tooth Shape	Hook	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
mm	mm	mm	mm			A1					
182	1,7	1,3	19,05	40	ATB	15°	••	••	-	FR10W002H	F03FS09701
182	1,7	1,3	19,05	60	ATB	15°	•	•••	-	FR10W003H	F03FS09702
184	1,6	1,0	20	24	ATB	25°	•••	•	-	FR11W010HC	F03FS10055
184	1,6	1,0	20	48	ATB	10°	•	•••	-	FR11W011HC	F03FS10056
190	1,5	1,0	30	18	ATB	25°	•••	•	-	FR13W010HC	F03FS10057
190	1,5	1,0	30	24	ATB	25°	•••	•	-	FR13W011HC	F03FS10058
190	1,5	1,0	30	48	ATB	15°	••	••	-	FR13W012HC	F03FS10059
190	1,5	1,0	30	60	ATB	10°	•	•••	-	FR13W013HC	F03FS10060

For miter saws




D	B	b	d	Z	Tooth Shape	Hook	NL	Freud Code	Art. No.
mm	mm	mm	mm			A1			
210	2,4	1,8	30	48	ATB	-5°	2/7/42	FR15W001M	F03FS09747
216	2,4	1,8	25,4	48	ATB	-5°	2/6/42	FR16W004M	F03FS09751
216	2,4	1,8	25,4	64	ATB	-5°	2/6/42	FR16W005M	F03FS09752
216	2,4	1,8	30	24	ATB	-5°	2/6/42	FR16W001M	F03FS09748
216	2,4	1,8	30	40	ATB	-5°	2/7/42	FR16W002M	F03FS09749
216	2,4	1,8	30	48	ATB	-5°	2/7/42	FR16W003M	F03FS09750
250	2,4	1,8	30	40	ATB	-5°	FT121	FR23W001M	F03FS09753
250	2,4	1,8	30	60	ATB	-5°	FT121	FR23W002M	F03FS09754
254	2,4	1,8	30	60	ATB	-5°	FT121	FR24W001M	F03FS09755
260	2,4	1,8	30	60	ATB	-5°	FT121	FR26W001M	F03FS09760
300	2,4	1,8	30	72	ATB	-5°	FT121	FR28W001M	F03FS09761
305	2,4	1,8	30	48	ATB	-5°	-	FR29W001M	F03FS09762
305	2,4	1,8	30	72	ATB	-5°	FT121	FR29W002M	F03FS09763
315	2,4	1,8	30	72	ATB	-5°	FT121	FR30W001M	F03FS09766

FT121: 2/7/42 + 2/9/46 + 2/9,5/46,5 + 2/10/60




For cordless miter saws



D	B	b	d	Z	Tooth Shape	Hook	NL	Freud Code	Art. No.
mm	mm	mm	mm			A1			
216	1,7	1,2	30	24	ATB	5°	-	FR16W006MC	F03FS10061
216	1,7	1,2	30	48	ATB	5°	-	FR16W007MC	F03FS10062
250	2,1	1,6	30	24	ATB	5°	-	FR23W003MC	F03FS10063
250	2,1	1,6	30	48	ATB	5°	-	FR23W004MC	F03FS10064
305	2,2	1,6	30	42	ATB	5°	-	FR29W004MC	F03FS10065
305	2,2	1,6	30	60	ATB	5°	-	FR29W005MC	F03FS10066
305	2,2	1,6	30	96	ATB	5°	-	FR29W006MC	F03FS10067

For small table saws





D	B	b	d	Z	Tooth Shape	Hook	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
mm	mm	mm	mm			A1					
190	2,0	1,3	30	24	ATB	15°	•••	•	2/7/42	FR13W001T	F03FS09767
190	2,0	1,3	30	48	ATB	5°	•	•••	2/7/42	FR13W002T	F03FS09768
190	2,4	1,6	Star	24	ATB	15°	•••	•	-	FR13W003T	F03FS09769
190	2,4	1,6	Star	48	ATB	5°	•	•••	-	FR13W004T	F03FS09770
220	2,6	1,6	30	48	ATB	10°	••	••	2/7/42	FR17W001T	F03FS09771
225	2,6	1,6	30	32	ATB	15°	•••	•	2/7/42	FR18W001T	F03FS09772
225	2,6	1,6	30	48	ATB	10°	••	••	2/7/42	FR18W002T	F03FS09773
250	2,8	1,8	30	24	ATB	20°	•••	•	2/6/42	FR23W001T	F03FS09774
250	2,8	1,8	30	40	ATB	15°	•••	•	2/6/42	FR23W002T	F03FS09775
250	2,8	1,8	30	60	ATB	10°	••	••	2/6/42	FR23W003T	F03FS09776
250	2,8	1,8	30	80	ATB	5°	•	•••	FT121	FR23W004T	F03FS09777
254	2,6	1,8	30	24	ATB	20°	•••	•	2/6/42	FR24W001T	F03FS09778
254	2,6	1,8	30	40	ATB	15°	•••	•	2/6/42	FR24W002T	F03FS09779
254	2,6	1,8	30	60	ATB	10°	••	••	FT121	FR24W003T	F03FS09780
254	2,6	1,8	30	80	ATB	5°	•	•••	FT121	FR24W004T	F03FS09781
255	2,8	1,8	25,4	40	ATB	15°	•••	•	-	FR25W002T	F03FS10134
255	2,8	1,8	25,4	60	ATB	15°	••	••	-	FR25W003T	F03FS10135
255	2,8	1,8	25,4	80	ATB	15°	•	•••	-	FR25W004T	F03FS10136
260	2,6	1,8	30	60	ATB	10°	••	••	-	FR26W001T	F03FS09782
260	2,6	1,8	30	80	ATB	5°	•	•••	FT121	FR26W002T	F03FS09783
300	2,5	1,8	30	48	ATB	15°	•••	•	2/10/60	FR28W001T	F03FS09784
300	2,5	1,8	30	72	ATB	10°	••	••	2/10/60	FR28W002T	F03FS09785
300	2,5	1,8	30	100	ATB	5°	•	•••	FT121	FR28W003T	F03FS09786
305	2,8	1,8	25,4	96	ATB	15°	•	•••	-	FR29W002T	F03FS10138
305	2,8	1,8	30	100	ATB	5°	•	•••	2/10/60	FR29W001T	F03FS09787
355	3,0	2,2	25,4	108	ATB	15°	•	•••	-	FR33W001T	F03FS10137

FT121: 2/7/42 + 2/9/46 + 2/9,5/46,5 + 2/10/60



For cordless small table saws



D	B	b	d	Z	Tooth Shape	Hook	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
mm	mm	mm	mm			A1					
210	2,0	1,4	30	24	ATB	25°	•••	•	-	FR15W001TC	F03FS10068
210	2,0	1,4	30	48	ATB	15°	•	•••	-	FR15W002TC	F03FS10069
216	2,0	1,4	30	24	ATB	25°	•••	•	-	FR16W001TC	F03FS10070
216	2,0	1,4	30	48	ATB	15°	•	•••	-	FR16W002TC	F03FS10071
254	2,1	1,6	30	24	ATB	25°	•••	•	-	FR24W005TC	F03FS10072
254	2,1	1,6	30	40	ATB	20°	••	••	-	FR24W006TC	F03FS10073
254	2,1	1,6	30	60	ATB	15°	•	•••	-	FR24W007TC	F03FS10074